



- Class II Configuration
- Efficiency Level VI
- Interchangeable Plugs for Worldwide Use
- Optional USB (5V only) or Cable Output
- Short Circuit Protection
- Overload Protection
- No Load Operation



Electrical Specifications

Input

Input Voltage	90-264VAC
Input Frequency	47-63 Hz
Input Current	<0.6A, 115VAC– 230VAC
Safety Isolation	3.0kVAC Input to Output
Inrush Current	<30A peak @ 115VAC, cold start at 25°C <60A peak @ 230VAC, cold start at 25°C
No Load Power	< 100mW

Output

Total Output	12W
Output Voltage	See table
Hold Up Time	>8.3 msec @ full load and 115VAC/60Hz input
Turn On Time	<3 seconds
Efficiency	Meets DOE level VI requirements
Minimum Load	No minimum load
Line Regulation	<± 1% of rated output voltage at full load

Protection

Overvoltage	150% Max. of rated voltage. Latching mode. Cycle AC for recovery
Short Circuit	Hiccup mode. Auto recovery.
Overcurrent	150% Max. of rated current. Auto-restart when fault removed.
Ingress	IP22 Compliant

Environmental & Operating

Operating Temperature	0°C to +60°C (Derate output power linearly from 100% at 40°C to 50% at 60°C)
Storage Temperature	-20°C to +85°C
Operating Altitude	<5000m
Operating Humidity	10% - 90% non-condensing
Storage Humidity	5% - 90% non-condensing
MTBF:	>100,000 hours per MIL-HDBK-217F at full load and 25°C ambient

Compliance

Safety Approvals	
USA	UL60950-1
Canada	cUL60950-1
Europe	TUV EN60950-1/A12: 2011 CB Report
EMC:	FCC Class B Radiated & Conducted CISPR22 Class B Radiated & Conducted EN55022 Class B Radiated & Conducted
Harmonic Currents	IEC 61000-3-2
Voltage Flicker	IEC 61000-3-3
Electrostatic Discharge	IEC 61000-4-2: 8kV Air, 4kV contact
Radiated Immunity	IEC 61000-4-3: 3V/m
EFT/Burst	IEC 61000-4-4: +/-1kV
Surge Immunity	IEC 61000-4-5: 2005 1kV diff, 2kV com
Conducted Immunity	IEC 61000-4-6: 3Vrms
Magnetic Field	IEC 61000-4-8: 1A/m
Dips / Interruptions	IEC 61000-4-11: 30% reduction for 500ms, >95% reduction for 10ms.

General

Dimensions	2.20"(56.0mm)L x 1.46"(37.0mm)W x 1.26"(32.0mm)H
AC Input	Interchangeable Plugs
Output Plug	Barrel Type: 5.5mm x 2.1mm x 9.5mm Center positive (others upon request) Optional USB output for 5V models
Weight	0.3 pounds

Your Partners in Power.....

Power Partners, Inc. | 43 Broad Street | Hudson, MA 01749

Tel: (978)567-9600 | Fax: (978)567-9601

Website: www.powerpartners-inc.com

Specifications subject to change.
PEAW12I: April 3, 2018



Models and Ratings Chart

Model No.	Output voltage	Output Current	Total Power	Output Regulation	Ripple & Noise (Vp-p)	Efficiency Level
PEAW12I-10-B1	5VDC	2.4A	12W	± 5%	100mV	VI
PEAW12I-10-USB	5VDC	2.4A	12W	± 5%	100mV	VI
PEAW12I-10-1-B1	6VDC	2.0A	12W	± 5%	100mV	VI
PEAW12I-11-B1	9VDC	1.33A	12W	± 5%	180mV	VI
PEAW12I-12-B1	12VDC	1.0A	12W	± 5%	250mV	VI
PEAW12I-13-B1	15VDC	0.8A	12W	± 5%	250mV	VI
PEAW12I-13-1-B1	18VDC	0.66A	12W	± 5%	350mV	VI
PEAW12I-13-2-B1	19VDC	0.63A	12W	± 5%	350mV	VI
PEAW12I-14-B1	24VDC	0.5A	12W	± 5%	350mV	VI

Notes:

- Ripple & Noise is measured using a 20MHz bandwidth oscilloscope with a 0.1uf ceramic capacitor and 4.7uf electrolytic capacitor in parallel across the output at full load and nominal line voltage.
- PEAW12I-10-USB has a standard USB A output port. All other models have a 4ft cable terminated with a 5.5 x 2.1mm barrel connector. Consult PPI for custom connectors.

Mechanical Outline

